

# CVT2 Wet Location Fixtures



**Description:** CVT2 Series Vapor Tight Fixtures are UL listed for damp and wet locations. CVT2 fixtures are fully dust and moisture resistant, and feature a fiberglass upper body, a permanent poured-in-place sealing gasket and high strength linear ribbed clear acrylic diffuser. CVT2 fixtures are available in 4' and 8' configurations.

**Standard Features:** Each standard CVT2 fixture includes:

- Universal gear-tray enables T5 or T8 lamp configuration, and eliminates metal strip reducing shipping weight and costs; easy retrofits
- MICRO4 Reflector is standard; 95% reflectivity increases fixture performance by 7% versus white ballast cover; batwing distribution provides uniform horizontal illumination; wider light distribution; efficacy improved by 10%
- Thermoformed linear ribbed lens geometry improves strength dramatically ensures strong, rigid seal strength
- Spring-mounted stainless-steel bracket kits are standard
- Each fixture includes fitting assembly for 1/2" rigid conduit
- High-strength Celcon latches
- Ballast Disconnect

**Ballast Specifications:** High performance instant start electronic ballasts are standard on all CVT2 Series Fixtures. Each ballast has minimum starting temp: 0F/-18C; maximum ambient temp: 104F/40C; >0.98 power factor; Universal (120-277VAC) Input Voltage; 50/60 Hz Input Frequency; UL/935 (Class P, Type HL, Type 1 outdoor) listed; 5 year warranty

## Commercial Lighting Company



4930 Leary Ave NW

Seattle, WA 98107

Ph (206) 682-6385 (800) 992-LITE

Fax (206) 624-6163

[WWW.COMMERCIALLIGHTINGCOMPANY.COM](http://WWW.COMMERCIALLIGHTINGCOMPANY.COM)

Ordering Information	Description
CVT248-232EBUNIV	4', 2-lamp T8
CVT248-332EBUNIV	4', 3-lamp T8
CVT248-254HOEBUNIV	4', 2-lamp T5HO
CVT296T-432EBUNIV	8', 4-lamp tandem T8
CVT296T-454HOEBUNIV	8', 4-lamp tandem T5HO

