

Recessed Direct / Indirect T5 Troffer Conversion Kit

Applications: Retail, Offices, Schools and Hospitals; i.e., Standard 15/16" grid ceilings



Available in 1, 2, or 3-Lamp Design (T5HO only)
Recessed Direct / Indirect T5 Fixture shown

General Description:

The KIB T5 Troffer Conversion Kit is a contemporary solution for standard 15/16" grid ceilings often popular in retail, office, school, and/or hospital applications. These conversion kits are perfect for replacement of 2 and 4-Lamp T12 parabolic or lensed troffer fixtures.

The Kit design incorporates a perforated metal basket that enhances the fixture, offering low glare capabilities and soft, balanced lighting.

Electrical Accessories:


- Factory installed ballast options; Low, Normal, High and 480v

Features:

- Can be used to replace parabolic or lensed troffers
- Tool-less installation
- Latch-free Basket
- Faceted reflector design
- Aluminum components
- Snap in and twist lock sockets
- Available with shunted or non-shunted sockets

***Reflector Material Type**

EA = 95% Enhanced Aluminum
WA = 91% White Aluminum



Existing Fixture	Input Watts	System Lumens
4-Lamp F40 T12	192	9120
2-Lamp F40 T12	96	4560
4-Lamp F34 T12	144	7930
2-Lamp F34 T12	72	3960
Retrofit Options	Input Watts	System Lumens
1-Lamp F54 T5	62/60	5000
2-Lamp F54 T5	121/115	10000
3-Lamp F54 T5	182/178	15000
1-Lamp F28 T5	31	2900
2-Lamp F28 T5	62/61	5800
1-Lamp F24 T5	29/27	2000
2-Lamp F24 T5	55/52	4000
1-Lamp F14 T5	17	1350
2-Lamp F14 T5	32	2700

Benefits:

- Soft and Balanced Lighting
- Low Glare
- Aesthetically pleasing
- Easy installation

Recessed Direct/Indirect T5 Conversion Kits Include:

- 1 Reflector
- 2 Mounting Brackets
- 5 Tex screws
- 2 End Caps
- 1 Perforated Basket
- 1 Lens
- 1 Access Door

KIB Recessed Direct/Indirect T5 Troffer Conversion Kit Ordering Guide

KIB	Lamps	Lamp Type	Fixture Length	Voltage	Reflector*	Ballast	Sockets
T5 Recessed Direct/Indirect Conversion Kit with Perforated Basket KIB	1-Lamp 2-Lamp 3-Lamp	T5 T5HO	02 = 2ft 04 = 4ft	14 Watt 24 Watt 28 Watt 54 Watt	EA = 95% WA = 91%	L = Low N = Normal H = High 4 = 480 Volt	FLS = Shunted FLN = Non-Shunted

COMMERCIAL LIGHTING COMPANY

Manufacturing & Assembly | Fluorescent Lighting Fixtures & Retrofit Kits

4930 Leary Avenue NW | Seattle, WA 98107
800-992-5483 toll free | 206-682-6385 office | 206-624-6163 fax

